


FUNE 6 TREFOLI



265 FILI Zincata

6x36WS+IWRC

anima metallica

crociata destra

crociata sinistra

Resistenza 1770 N/mm²

Resistenza 1960 N/mm²

265 WIRES Galvanized

6x36WS+IWRC

steel core

right regular lay

left regular lay

Tensile rope grade 1770 N/mm²

Tensile rope grade 1960 N/mm²

Diametro fune Rope diameter	Diametro fili esterni Outer wires diameter	Peso per metro Weight for meter	Carico rottura minimo MBL			
			1770 N/mm ²		1960 N/mm ²	
			kN	kg	kN	kg
10	0,56	0,42	64,00	6530	70,00	7140
11	0,62	0,51	77,00	7850	84,70	8640
12	0,67	0,60	95,00	9690	100,80	10280
13	0,73	0,71	110,00	11220	118,50	12080
14	0,79	0,82	129,00	13150	137,40	14010
15	0,84	0,95	144,00	14680	157,80	16090
16	0,90	1,08	165,00	16820	179,50	18300
18	1,01	1,36	210,00	21410	227,00	23140
20	1,12	1,68	259,20	26430	280,50	28600
22	1,24	2,03	313,50	31960	339,50	34610
24	1,35	2,42	373,00	38030	404,00	41190
26	1,46	2,84	438,00	44650	474,00	48320
28	1,57	3,29	499,00	50870	549,00	55970
30	1,69	3,78	578,00	58920	630,00	64230
32	1,80	4,30	651,00	66370	717,00	73090
34	1,91	4,86	735,00	74930	809,00	82470
36	2,02	5,44	824,00	84000	906,00	92360
38	2,13	6,06	922,00	93990	1010,00	102960
40	2,25	6,72	1020,00	103980	1119,00	114070
42	2,36	7,41	1120,00	114170	1233,00	125690
44	2,47	8,13	1230,00	125390	1353,00	137930
46	2,58	8,89	1345,00	137110	1478,00	150670
48	2,70	9,68	1460,00	148830	1610,00	164120
50	2,81	10,50	1585,00	161570	1745,00	177880
52	2,92	11,36	1715,00	174830	1887,00	192360
54	3,03	12,25	1850,00	188590	2035,00	207450
56	3,15	13,17	1990,00	202860	2187,00	222940
58	3,26	14,13	2135,00	217640	2335,00	238030
60	3,37	15,12	2280,00	232420	2500,00	254850