


FUNI

FUNE 6 TREFOLI



265 FILI Zincata
 6x36WS+IWRC
 anima metallica
 crociata destra
 crociata sinistra
 Resistenza 2160 N/mm²

265 WIRES Galvanized
 6x36WS+IWRC
 steel core
 right regular lay
 left regular lay
 Tensile rope grade 2160 N/mm²

Diametro fune Rope diameter mm	Diametro fili esterni Outer wires diameter mm	Peso per metro Weight for meter kg	Carico rottura minimo MBL	
			kN	kg
10	0,56	0,42	81,80	8340
11	0,62	0,51	98,90	10090
12	0,67	0,60	117,80	12010
13	0,73	0,71	138,30	14100
14	0,79	0,82	160,30	16350
15	0,84	0,95	184,00	18760
16	0,90	1,08	209,50	21360
18	1,01	1,36	265,00	27020
19	1,07	1,52	295,00	30080
20	1,12	1,68	326,50	33290
22	1,24	2,03	396,00	40370
24	1,35	2,42	471,50	48070
26	1,46	2,84	553,00	56380
28	1,57	3,29	640,00	65240
30	1,69	3,78	734,00	74830
32	1,80	4,30	835,50	85170
34	1,91	4,86	920,00	93790
36	2,02	5,44	1030,00	105000
38	2,13	6,06	1150,00	117230
40	2,25	6,72	1255,00	127940
42	2,36	7,41	1385,00	141190
44	2,47	8,13	1515,00	154440
46	2,58	8,89	1655,00	168710
48	2,70	9,68	1775,00	180940
50	2,81	10,50	1926,00	196340
52	2,92	11,36	2082,00	212240
54	3,03	12,25	2240,00	228340
56	3,15	13,17	2370,00	241600
58	3,26	14,13	2540,00	258920
60	3,37	15,12	2700,00	275230